

PEN RED LIGHT SOURCE

CARRIER-GRADE
VISUAL LASER RED
LIGHT PEN FAU




LUMINOUS STABLE LIGHT SOURCE STRONG

STRONG PENETRATING FORCE CAN EASILY DETECT THE
CONNECTION OF THE LINE




MULTI-POWER OPTION


THREE KINDS OF POWER MEET THE REQUIREMENTS



DR-201 (1mw)



DR-210 (10mw)



DR-220 (20mw)

5KM



10KM



20KM

FREE CHOICE OF THREE GEARS



OFF



FLICKER



CONSTANT

SPECIAL LASER HEAD DESIGN

AVOID DAMAGE CAUSED BY ACCIDENTAL COLLISIONS



2.5MM UNIVERSAL INTERFACE

IT IS SUITABLE FOR SC/FC INTERFACES, AND THE EXTERNAL LC CONVERSION ADAPTER CAN BE CONNECTED TO THE LC INTERFACE



SC INTERFACE



FC INTERFACE

LOW VOLTAGE ALARM

A LOW POWER ALARM CIRCUIT PROMPTS TO REPLACE THE BATTERY BEFORE IT RUNS OUT OF POWER

CONSTANT POWER OUTPUT

SPECIAL DRIVE CIRCUIT IS USED TO ENSURE CONSTANT POWER OUTPUT WHEN THE POWER IS EXHAUSTED

HIGH TEMPERATURE AGING TEST

AFTER +50°C/8 HOURS HIGH TEMPERATURE AGING TEST TO ENSURE RELIABILITY AND STABILITY

HIGH QUALITY METAL CASING

DURABLE AND STRONG AGAINST FALLS



SPECIFICATION PARAMETER

MODEL: TFN PEN RED LIGHT SOURCE
CENTRAL WAVELENGTH: 650NM \pm 10NM
LIGHT SOURCE TYPE: FP-LD
OUTPUT POWER: 10MW
MODULATION MODE (HZ) : CW, 2
OPTICAL FIBER TYPE: SM MM
POWER SUPPLY: 2 1.5VAA BATTERIES
DURATION (H) :60 (1MW/650NM)
OPERATING TEMPERATURE (°C):-10~+45
STORAGE TEMPERATURE (°C) : -40~+70
OVERALL DIMENSION (MM) : 15MM*180MM
WEIGHT (G) : 120 (WITHOUT BATTERY)



PRODUCT LIST



PACKING BOX



PROTECTION PACK



TWO AA BATTERIES



SPECIFICATION